



The Bosch Highflow series: High quality, High efficiency hot water for your home.

Bosch electronic Highflow units are compact, space-saving and easy to install. This range is specifically designed for maximum energy efficiency and environmental protection, providing a minimum of 5.5+ star performance rating. With a Bosch Highflow you are assured continuous hot water, while saving money and caring for the environment.

Range includes:

- ▶ 6 Star 17L and 21L models
- ▶ Install up to 4 optional temperature controllers
- ▶ Antifrost feature as standard



BOSCH

Hot Water & Heating



The Bosch Highflow Range

Specifications	Bosch 17e	Bosch 21e	Bosch 26e
Part Number	YS1780RA	YS2180RA	YS2670RAH
Installation	External	External	External
Ignition	Electronic	Electronic	Electronic
L/min (25°C rise)	17	21	26
No. of bathrooms	1	1-2	2-3
Min. operating inlet water pressure (kPa)	200	200	100
Max. inlet water pressure (kPa)	1000	1000	1000
Mj/H	130	159	200
Star Rating	6.00	6.10	5.53
Antifrost	Standard	Standard	Standard
Solar & High temperature compatible	No*	No*	Yes
50°C Limited Part Number	YS1780RA5	YS2180RA5	YS2670RA5
Gas Type	NG/LPG	NG/LPG	NG/LPG
Electrical Supply	230 VAC - 240V 50 Hz (10amp weatherproof power point required within 500 mm of the unit)		
Temperature Controllers	Up to 4 temperature controllers can be installed		
Unit Height (mm)	520	520	650
Unit Width (mm)	350	350	350
Unit Depth (mm)	170	170	170
Carton Weight (Kg)	18	19	22
Domestic Warranty			
Parts and Labour	3 Years	3 Years	3 Years
Heat Exchanger (part only)	10 Years	10 Years	10 Years
Pipe Connection Size			
Natural gas (NG)	20 mm (3/4")	20 mm (3/4")	20 mm (3/4")
LP gas	20 mm (3/4")	20 mm (3/4")	20 mm (3/4")
Cold Water	20 mm (3/4")	20 mm (3/4")	20 mm (3/4")
Hot Water	20 mm (3/4")	20 mm (3/4")	20 mm (3/4")

*Solar & High Temperature specific models are also available (YS1770RAH, YS2170RAH)

Features & Benefits

- ▶ 5.5+ star energy efficiency
- ▶ Continuous flow technology
- ▶ Compact design
- ▶ All new Highflow models are capable of utilising up to 4 optional temperature controllers
- ▶ Suitable for 1-3 bathroom homes
- ▶ 50°C limited models available
- ▶ Antifrost as standard on all models
- ▶ External installation only
- ▶ 3 year parts and labour and 10 year heat exchanger warranty (part only)

Premium Controller



YPRM67XBN



YPRS67XBN

- > Easy to use – select desired temp and turn on tap
- > Environmentally friendly – limit shower time
- > Bath fill – auto stop
- > Consistent delivery – no more temperature fluctuations when someone flushes a toilet

Lockable Recess Box

RBHF50L (17e & 21e)
RBHF26L (26e)

Ideal for new homes, Bosch lockable recess boxes allow Highflow systems to be recessed, saving space and securing your investment. The lockable recess box can also be painted to suit the appearance of your home.

Brick opening dimensions

RBHF50L & RBHF26L

Height: 930

Width: 345

Depth: 145

*Minimum dimensions



Contact Us: 1300 30 70 37 or visit www.bosch-climate.com.au