

SIMPLY WOODCARE

Dexpress Deck & Timber Stain

Product Code: SDEX

Product description

For a long lasting finish that protects your decking, weatherboards, screening and garden furniture in their best light, choose Simply Woodcare Dexpress Deck and Timber Stain. Dexpress will enhance the look and longevity of Australia's favourite decking timbers including Merbau, Spotted Gum and Treated Pine, it's tested and proven to withstand the harsh Australian climate.



Key Features

- ✓ Long-lasting cutting edge formula
- ✓ Lasts 3-4 times longer than traditional decking oils
- ✓ UV & mould resistant
- ✓ Quick drying
- ✓ Simple to use with a great range of colours

Where to Use

Decking, weatherboards, garden furniture, cladding, garage doors, walkways, fencing, screens & pergolas.

Typical properties

Gloss	Low lustre
Application tools	Brush, mohair applicator, mohair roller, lambswool applicator.
Clean-up	Water
Dry time	Touch Dry 20 minutes Recoat 2 hours
Coverage	Up to 12m ² /L
Colour	Natural, Merbau & Stain Tint.
Sizes	1Lt, 4Lt, 10Lt
VOC	57 g/L
Volume solids	27%
Film build	Wet 100um Dry 27um

Surface Preparation	
General Surface Preparation	<ol style="list-style-type: none"> 1. Ensure all surfaces are clean, bare, dry and free of mould, wax, grease and other contaminants prior to applying Dexpress. The presence of contaminants will cause rejection and delamination 2. Clean the surface thoroughly with Simply Woodcare Wood Cleaner following application instructions 3. Rinse surface clean using a pressure washer and allow to dry 4. Check timber is ready for coating by sprinkling with water. Ensure water penetrates the timber otherwise a repeat application of wood cleaner is required 5. Fill cracks, nail holes and imperfections with Simply Woodcare Wood Putty. Sand smooth and dust down
New Unweathered Timber	<ol style="list-style-type: none"> 1. Prepare unweathered timber with Simply Woodcare Rapid Prep according to label instructions. 2. If the timber has been weathered refer to General Surface Preparation. 3. Rinse clean with a pressure washer. 4. Check timber is ready for coating by sprinkling with water. 5. Ensure water penetrates the timber otherwise a repeat application of Rapid Prep is required.
Previously Coated Surfaces	<ol style="list-style-type: none"> 1. For best results we recommend removal of all previous coatings 2. If coating is in sound condition apply one coat of Simply Woodcare Dexpress in an inconspicuous area and allow to dry for 24 hours. 3. Cut an X in the surface and press tape firmly over the cut. Pull the tape off and inspect. If any coating has stuck to the tape the surface will need to be thoroughly stripped before recoating.

Application
<p>DO NOT apply if ambient temperature is less than 10°C or greater than 30°C or if conditions will drop below 10°C during the drying period. Under warmer conditions refer to Thinning advice.</p> <ul style="list-style-type: none"> • To extend the life of the coating, choose a colour that most closely resembles the timber to be coated. • Do not apply to hot surfaces or in direct sunlight. • Stir thoroughly before and during application using a broad flat stirrer. • Apply two coats by brush or applicator at recommended coverage rate. • Apply along the length of the board including all exposed edges and end grain. • Appropriate preparation and application thickness is vital to the performance and longevity of the product. • All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperatures or higher humidity drying times will be extended. • Water-based coatings can turn milky and soften if they are exposed to high levels of moisture during the drying phase. Once the moisture or water has evaporated the coating will return as normal however please treat with care while this takes place. <p>Please check the colour for accuracy prior to application. Haymes Paint accepts no responsibility for the application of incorrect colours.</p> <p>IMPORTANT DO NOT apply if rain is expected within 24 hours of application. Should rain or dew come into contact with the freshly applied finish white marks can appear. Pooled water should be removed using a soft mop. The white marks will disappear as the coating cures. The appearance of white marks will not affect the long term performance of the coating. Depending on weather conditions the finish may initially feel tacky. This tackiness does not prevent use of the surface and will disappear as the coating cures.</p> <p>Simply Woodcare Dexpress has a lifespan 3-4 times that of conventional decking oils under similar conditions provided surface preparation and application are carried out according to the instructions. North and West facing decks are exposed to more extreme weather conditions and will need more frequent maintenance than other orientations.</p>

Thinning

Thinning is not recommended. However, under warm conditions up to 50ml of water can be added per litre of product to ease application.

Care and Maintenance

Protect the coating from abrasive contact for seven days. Periodically cleaning the surface with a mild detergent or Simply Woodcare Wood Cleaner will rejuvenate the surface and extend the service life by removing contaminants, which can damage the surface. It is important to reapply Dexpress when the coating begins to show signs of wear.

Storage

Protect from extremes of temperature. Store between 5°C and 30°C.

Safety & First Aid

Keep out of reach of children. Avoid contact with skin and eyes and inhalation of vapour. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using. Handling and usage of this product must be carried out under well-ventilated conditions that prevent inhalation of vapours. If affected by inhalation, remove to fresh air. If breathing difficulty persists or occurs later, consult a doctor. If swallowed, DO NOT INDUCE VOMITING. Drink plenty of water and seek medical advice. Contact a doctor or Poisons Information Centre (Phone 13 11 26). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation develops or persists seek medical advice. In case of eye contact, hold eyes open and flush with water for at least 15 minutes and seek medical advice.

Protect our environment

DO NOT pour any leftover product down the drain. Retain in a marked, sealed container for future use or disposal via special chemical waste collection programs. Dried empty containers can be recycled and should be disposed of via recycling facilities. Do not re-use empty containers.

Manufacturer's comment

This product has been designed as part of a totally integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of Safety Data and Product Information Sheets from Haymes Paint www.haymespaint.com.au. We are continually updating materials and methods, so please ensure you have the latest information.

Disclaimer

The information provided is correct at the time of preparation; however it is the responsibility of those using this information to check that it is current prior to specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time, those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices are in compliance with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded.

Henry Haymes Pty Ltd
A.B.N. 14 004 201 638
Waringa Drive
Wendouree Industrial Estate
Ballarat Vic 3350
Free call 1800 033 431
Free fax 1800 801 892
www.haymepaint.com.au

Date of Preparation 26/02/2018